



P/N	L/(M)	T/(MM)
26-0020MF	2	30
26-0030MF	3	45
26-0050MF	5	75
26-0100MF	10	150

PIN OUT

P1	P2	P1	P2
Red coax conductor	1	9	9
Green coax conductor	2	10	10
Blue coax conductor	3	11	11
	4	12	12
Red coax drain	5	13	13
Green coax drain	6	14	14
Blue coax drain	7	15	15
	8	shell	Drain shell

NOTES:

- 1:100% short,open and miss wire test.
- 2:Cable marking:CONNEKT GEAR AWM STYLE 2919 80°C 30V LOW VOLTAGE Computer Cable RoHS & REACH Compliant

NO.	MATERIAL	DESCRIPTION	QTY.	UNIT
⑥	OUTER MOULDED	BLACK 45P PVC	0.048	KG
⑤	INNER MOULDED	LDPE	0.021	KG
④	SCREW	#4-40UNC 2.3*45.5MM,BLACK PVC	4	PCS
③	CONNECTOR	HDB 15PIN/FEMALE,BLUE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN,	1	PCS
②	CONNECTOR	HDB 15PIN/MALE,BLUE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN,	1	PCS
①	CABLE	(1C*7/0.1BC+FPE+D+PVC)*3C+9C*7/0.10BC+AL+D+B,JACKET:BLACK PVC, OD:8.0±0.2MM	L	M

LItemref	Quantity	Title/Name,designation,material,dimension etc		Article No./Reference	
Designed by	Checked by	Approved by - date	File name	Date	Scale
		JUL 27.2015		JUL 27.2015	FREE
ANGLE:			VGA(3+9),HDB15M-HDB15F,30AWG,BLACK		
UNIT:MM			26-0020MF,26-0030MF 26-0050MF,26-0100MF	Edition	Sheet
				1	1/1