



P/N	L/mm	T/mm
26-0010MM	1000	20
26-0020MM	2000	30
26-0030MM	3000	50
26-0050MM	5000	80
26-0100MM	10000	100

NOTES:

1. Open/Short/Intermittence: 100%
2. Insulation Resistance: DC300V 10mS 10MΩ (Min)
3. Conductive Resistance: 10Ω (Max)
4. RESOLUTION: 1440*900@60Hz
5. RoHS & REACH COMPLIANT

P1	P2	P1	P2
1	1	9	9
2	2	10	10
3	3	11	11
4	4	12	12
5	5	13	13
6	6	14	14
7	7	15	15
8	8	SHELL	SHELL

⑤	SCREW	4-40 UNC, NICKEL-PLATED, PVC MOLDED	2	PCS
④	MOLDED	45P BLACK PVC		G
③	MOLDED	LDPE		G
②	CONNECTOR	VGA 15P MALE, GOLD PLATED PIN, BLUE INSULATION, NICKEL PLATED SHELL	2	PCS
①	CABLE	[(7/0.10TC)+FPE+D(7/0.10TC)+AL+PVC]*3C+7/0.10TC*9C+AL+D(7/0.10TC)+B(16*5/0.12AL-MG), BLACK PVC DENTATE JACKET, OD:8.0±0.2MM MARKING:connektgear AWM STYLE 2919 80°C 30V LOW VOLTAGE Computer Cable RoHS & REACH Compliant	L	MM
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT

Ltemref	Quantity	Title/Name, designation, material, dimension etc			Article NO./Reference	
Designed by FLY	Checkde by HELEN	Approved by - date 2024. 11. 28	File name	Date 2024. 11. 28	Scale FREE	
ANGLE:		VGA(3+9)M-M 30AWG			Edition 1	Sheet 1/1
UNIT:MM						